

STANDARD EQUIPMENT

- Available power options: Petrol Honda engine i-GX 390 8,7 kW, Diesel Kubota Engine, Eco (AC+Battery), Eco Pro, Hybrid/Dual Power (Honda Petrol+AC+Battery)
- Hydraulic steering and transmission on rubber tracks
- Extendable tracks 775/955 mm
- Inclinometer while transferring with sound alarm
- Hydraulic set-up with 4 independent outriggers, of the fixed type
- Turntable rotation at 360°
- CANBUS electronics
- Steel made telescopic double articulated boom with jib
- Hydraulic and electric lines inside the boom
- Aluminium cage 140x70x110 cm
- Cage with automatic self-levelling
- Cage with support of fast disassembling for narrow passages
- Geometric platform without any outreach-limiting device
- Load sensor on the cage
- Cable control with mini-display for ground/cage
- 230 V AC electric plug on the cage
- CE Mark homologation certificates, manuals, stickers and spares book in English language




**PETROL
DIESEL**



**ECO
ECO PRO**



HYBRID DUAL



AUTOMATION PACK (AUTOMATIC SET-UP + SELF-LEVELLING OF THE OUTRIGGERS + "RETURN TO HOME" FUNCTION)



AIR/WATER SUPPLEMENTARY LINE ALONG THE BOOM WITH INTERNAL HOSE




NON-MARKING TRACKS



CONTROL FOOT PEDAL ON THE CAGE



CAGE FOR ONE MAN 70x70x110 CM



FIBER GLASS CAGE FOR ONE MAN 70x70x110 CM



PADS WITH STOP FOR OUTRIGGERS



BASKET ROTATION 90°+90°



DIAGNOSTIC CABLE KIT



GROUNDING CABLE INSIDE THE BOOM (IN PLACE OF AIR/WATER PIPE)



CUSTOMIZED COLOURS



LED LIGHT




RADIO CONTROL WITH MINI DISPLAY



INTER-PHONIC COMMUNICATION SYSTEM



ELECTRONIC ANEMOMETER



LIFTING HOOK IN PLACE OF THE BASKET 230-250 kg



DRINK HOLDER IN THE BASKET



HANDS HEATER IN THE BASKET



EMERGENCY ELECTROPUMP KIT



SINGLE-PHASE ELECTRIC MOTOR 230 V AC - 2,2 kW WITH STARTER BATTERY CHARGER
AVAILABLE ONLY FOR PETROL AND DIESEL VERSIONS

PRELIMINARY