

STANDARD EQUIPMENT

- Available power options: Petrol Honda engine i-GX 390 8,7 kW, Diesel Kubota Engine, Eco (AC+Battery), Eco Pro, Hybrid/Dual Power (Honda Petrol+AC+Battery)
- Hydraulic steering and transmission on rubber tracks
- Extendable tracks 775/955 mm
- Inclinometer while transferring with sound alarm
- Hydraulic set-up with 4 independent outriggers, of the fixed type
- Turntable rotation at 360°
- CANBUS electronic
- Steel made telescopic double articulated boom with jib
- Hydraulic and electric lines inside the boom
- Aluminium cage 140x70x110 cm
- Cage with automatic self-levelling
- Cage with hydraulic rotation 90°+90°
- Cage with support of fast disassembling for narrow passages
- Geometric platform without any outreach-limiting device
- Load sensor on the cage
- Cable control with mini-display for ground/cage
- 230 V AC electric plug on the cage
- CE Mark homologation certificates, manuals, stickers and spares book in English language



**PETROL
DIESEL**



**ECO
ECO PRO**



HYBRID DUAL



AUTOMATION PACK (AUTOMATIC SET-UP + SELF-LEVELLING OF THE OUTRIGGERS + "RETURN TO HOME" FUNCTION)



AIR/WATER SUPPLEMENTARY LINE ALONG THE BOOM WITH INTERNAL HOSE



NON-MARKING TRACKS



CONTROL FOOT PEDAL ON THE CAGE




CAGE FOR ONE MAN 70x70x110 CM



FIBER GLASS CAGE FOR ONE MAN 70x70x110 CM



PADS WITH STOP FOR OUTRIGGERS



DIAGNOSTIC CABLE KIT



GROUNDING CABLE INSIDE THE BOOM (IN PLACE OF AIR/WATER PIPE)



SINGLE-PHASE ELECTRIC MOTOR 230 V AC - 2,2 kW WITH STARTER BATTERY CHARGER
AVAILABLE ONLY FOR PETROL AND DIESEL VERSIONS



CUSTOMIZED COLOURS



LED LIGHT



RADIO CONTROL WITH MINI DISPLAY



INTER-PHONIC COMMUNICATION SYSTEM



ELECTRONIC ANEMOMETER



LIFTING HOOK IN PLACE OF THE BASKET 230-250 kg



DRINK HOLDER IN THE BASKET



HANDS HEATER IN THE BASKET



EMERGENCY ELECTROPUMP KIT

PRELIMINARY