



SPIDER LIFT

With **Us**, You can



















AVAILABLE OPTIONS

STANDARD EQUIPMENT

- **CANBUS** electronics
- Hydraulic steering and transmission on rubber tracks with 2 speeds
- Hydraulic set-up with 4 independent outriggers, of the fixed type
- 2 aluminium made articulated double telescopic booms
- Safe working load 200 kg
- Aluminium cage 140x70x110 cm
- Cage with automatic self-levelling
- Cage with hydraulic rotation 90° + 90°
- Cage equipped with support of fast
- disassembling for narrow passages
- Boom slewing under any condition of load and set-up at 360°
- Electric and proportional controls and dual panel: cage panel and ground panel
- 230VAC electric plug on the cage
- CE Mark homologation certificates, manuals, stickers and spares book in English language







AIR/WATER SUPPLEMENTARY LINE ALONG THE BOOM WITH **INTERNAL HOSE**



CUSTOMIZED COLOURS



PROTECTION OF OUTRIGGERS' **CYLINDERS**



LED LIGHT



AUTOMATIC SET-UP AND SELF-LEVELLING OF THE OUTRIGGERS



RADIO CONTROL



BASKET ANTI-COLLISION KIT WITH ULTRASONIC SENSORS AND



INTER-PHONIC COMMUNICATION SYSTEM



NON-MARKING TRACKS



ELECTRONIC ANEMOMETER



CONTROL FOOT PEDAL ON THE CAGE



DRINK HOLDER IN THE BASKET



PADS FOR OUTRIGGERS



HANDS HEATER IN THE BASKET



"RETURN TO HOME" FUNCTION



EMERGENCY ELECTROPUMP KIT



DIAGNOSTIC CABLE KIT



24+6 MONTHS OF WARRANTY ON THE BATTERY



LOAD CELL







