

With **Us**, You can



HIGH GREEN SAFE

	19 m
	8,5 m
	200 kg
	Bi-energy Eco
	Crawlers Wheels

STANDARD EQUIPMENT

- CANBUS electronics
- Hydraulic steering and transmission on rubber tracks with 2 speeds
- Hydraulic set-up with 4 independent outriggers, of the fixed type
- 2 aluminium made articulated double telescopic booms
- Safe working load 200 kg
- Aluminium cage 140x70x110 Wcm
- Cage with automatic self-levelling
- Cage with hydraulic rotation 90° + 90°
- Cage equipped with support of fast disassembling for narrow passages
- Boom slewing under any condition of load and set-up at 360°
- Electric and proportional controls and dual panel: cage panel and ground panel
- 230VAC electric plug on the cage
- CE Mark homologation certificates, manuals, stickers and spares book in English language

BI-ENERGY (Diesel + AC)



ECO (AC + Battery)



AIR/WATER SUPPLEMENTARY LINE ALONG THE BOOM WITH INTERNAL HOSE



AUTOMATIC SET-UP AND SELF-LEVELLING OF THE OUTRIGGERS



BASKET ANTI-COLLISION KIT WITH ULTRASONIC SENSORS AND LASERS




NON-MARKING TRACKS



CONTROL FOOT PEDAL ON THE CAGE



PADS FOR OUTRIGGERS



DIAGNOSTIC CABLE KIT



EMERGENCY ELECTROPUMP KIT



CUSTOMIZED COLOURS



LED LIGHT



RADIO CONTROL



INTER-PHONIC COMMUNICATION SYSTEM



ELECTRONIC ANEMOMETER



DRINK HOLDER IN THE BASKET



HANDS HEATER IN THE BASKET

