


With **Us**, You can



**HIGH
GREEN
SAFE**



25 m



10,6 m



250 kg



Bi-energy
Eco



Crawler
Wheels



STANDARD EQUIPMENT

- CANBUS electronics
- Hydraulic transmission on non-marking rubber tracks with 2 speeds
- Hydraulic set-up with 4 independent outriggers, of the rotating type
- 2 aluminium made articulated double telescopic booms
- Safe working load 120/250 kg
- Aluminium cage 140x70x110 cm
- Cage with automatic self-levelling
- Cage with hydraulic rotation 90° + 90°
- Cage equipped with support of fast disassembling for narrow passages
- Boom slewing under any condition of load and set-up at 360°
- Area limiting system according to load and set-up (supplementary moment sensing system)
- Electric and proportional controls and dual panel: cage panel and ground panel
- 230VAC electric plug on the cage
- CE Mark homologation certificates, manuals, stickers and spares book in English language

BI-ENERGY (Diesel + AC)



ECO (AC + Battery)



HYDRAULIC WIRE-WINCH OF 250 KG



AIR/WATER SUPPLEMENTARY LINE ALONG THE BOOM WITH INTERNAL HOSE



PROTECTION OF OUTRIGGERS' CYLINDERS



AUTOMATIC SET-UP AND SELF-LEVELLING OF THE OUTRIGGERS



BASKET ANTI-COLLISION KIT WITH ULTRASONIC SENSORS AND LASERS




CONTROL FOOT PEDAL ON THE CAGE




PADS FOR OUTRIGGERS



"RETURN TO HOME" FUNCTION



DIAGNOSTIC CABLE KIT



LOAD CELL



CUSTOMIZED COLOURS



LED LIGHT



RADIO CONTROL



INTER-PHONIC COMMUNICATION SYSTEM



ELECTRONIC ANEMOMETER



DRINK HOLDER IN THE BASKET



HANDS HEATER IN THE BASKET



EMERGENCY ELECTROPUMP KIT



24+6 MONTHS OF WARRANTY ON THE BATTERY

